



COMMERCIAL DEHUMIDIFIER

250 PINT MODELS



	1PACD250
UPC	8-42149-02610-3
WATER REMOVAL CAPACITY (90°F, 90% RH)	250 pts./Day (31.25 gal./Day)
WATER REMOVAL CAPACITY (80°F, 60% RH)	142 pts./Day (17.75 gal./Day)
POWER SUPPLY	15AMP 115V
RATED POWER (W)	1180
RATED CURRENT (A)	10.4
DEFROST TYPE	Hot Gas Bypass
TIMER (hr.)	1-24
OPERATING TEMPERATURE	33°F – 100°F
REFRIGERANT	R410A
WEIGHT (Net/Gross) (lbs.)	137/147
PRODUCT SIZE (WxHxD) (in.)	21 x 38 x 22
PACKAGE SIZE (WxHxD) (in.)	23 ^{13/16} x 40 x 25
DRAIN HOSE LENGTH (ft.)	40
WASHABLE AIR FILTER	Yes

COMMERCIAL APPLICATIONS

- Manufacturing, printing, or packing/shipping facility
- Warehouses and records/media storage rooms
- Indoor pools, health clubs, and gymnasiums
- Hospitals & pharmaceutical labs
- Temporary office or school trailers
- Computer rooms
- Supermarkets, restaurants and bakery
- Large plants (water treatment, power, etc.)
- Museums, libraries, and art galleries
- Large basement or attic
- Any area affected by humidity from flooding, water leakage, or natural disasters
- Green houses



5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us