





Fasson® Products

MORE THAN 35 YEARS OF TRUSTED PERFORMANCE

Avery Dennison provides high quality Fasson brand pressure-sensitive HVAC/R tapes that deliver a fast, permanent bond providing an airtight moisture barrier for sealing duct board, flexible duct and insulation facings.

Contractors can chose from a complete line of foil, FSK, film and cloth duct tapes. Fasson® 0800 and Fasson® 0810 tapes carry a 20-year limited product warranty.

FOR BEST RESULTS

Fasson brand tapes adhere best on clean dry surfaces. For a strong bond, maintain tension when applying tape and then squeegee tape flat. Be sure to store tape in a cool, dry place and to rotate stock.





HVAC FASTENING SYSTEMS

Product	Description	Available Sizes	Rolls / Case	Order Number
Fasson® 0810	2 mil, high tensile strength aluminum foil, meets UL® standard 181A-P & B-FX for high performance closure systems on rigid fiberglass duct board and flexible duct, uses a 2.6 mil, white, high shear, acrylic adhesive that carries a 20-year limited warranty .	2.5" x 60 yds. 3.0" x 60 yds.	16 16	87412 02160180 87412 03000180
Fasson® 0800	2 mil, high tensile strength aluminum foil, meets UL® standard 181A-P & B-FX for high performance closure systems on rigid fiberglass duct board and flexible duct; uses a 2.4 mil, high shear, acrylic adhesive that carries a 20-year limited warranty ; economically priced.	2.5" x 60 yds. 3.0" x 60 yds.	16 16	56477 02160180 56477 03000180
Fasson® 0817	2 mil, dead-soft aluminum foil, coated one side with a 2 mil, quick stick, cold-temperature synthetic rubber-based adhesive. Features a strong bond to a variety of surfaces. UL® 723 classified.	2.0" x 50 yds. 3.0" x 50 yds.	24 16	56384 02000150 56384 03000150
Fasson® 0827	A tri-directional Foil Scrim Kraft (FSK) facestock that matches FSK faced insulation. Coated on one side with an aggressive, 2 mil, quick-stick, cold-temperature synthetic rubber-based adhesive. UL® 723 classified.	3.0" x 50 yds.	16	56535 03000150

CLOTH DUCT TAPES

Product	Description	Available Sizes*	Color	Order Number
Fasson® 950	10 mil, economy grade, cloth duct tape with a maximum performance temperature of 200°F. UL® 723 classified.	48mm x 55m	Black Silver	58984 01280180 58983 01280180
Fasson® 955	12 mil, metalized cloth duct tape with a maximum performance temperature of 200°F. UL® 723 classified.	48mm x 55m 72mm x 55m	Metalized Metalized	58988 01280180 58988 02270180
Fasson® 957	14 mil, UL® 181B-FX classified, Premium HVAC Grade cloth duct tape with a maximum performance temperature of 200°F. Heavy duty polyethylene and premium cloth ensure an airtight moisture barrier.	48mm x 55m 48mm x 55m 72mm x 55m	Black Metalized Metalized	58306 01280180 58307 01280180 58307 02270180

FILM TAPES

Product	Description	Available Sizes*	Color	Order Number
Fasson® FAS-FLEX	Printed metallized BOPP used for connecting, joining and sealing flexible air ducts. UL® 181B-FX classified.	48mm x 110m 48mm x 110m	Metalized Black	58343 01280360 58342 01280360
Fasson® Line Set Tape	UV-resistant, 1.4 mil acrylic adhesive film tape designed for taping elastomeric insulation on HVAC line sets.	48mm x 55m	Black	57656 01280180

ACCESSORIES

Product	Description	Available Sizes	Cans / Case	Order Number
Fasson® 1000S	High viscosity, excellent tack, multi-purpose spray adhesive for most lightweight materials. Specially formulated for fast and secure bonds, excellent properties for bonding dissimilar substrates and VOC compliant. Designed to meet current government requirements.	17 fluid ounces	12	589390

^{* 48}mm = 24 rolls per case 72mm = 16 rolls per case

Proud Members Of:









To learn more, contact your account manager, or visit: tapes.averydennison.com



ADV#0012, 5/2023, POD

For more information on technical performance and printing recommendations, please refer to the respective datasheets. Please note that the Avery Dennison product range and service offering can be subject to changes. For an accurate overview, please check our website tapes.averydennison.com or contact your local Avery Dennison sales representative.

DISCLAIMER — © 2023 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison. All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see tapes.averydennison.com/content/pt-responsive/na/en/home/terms-and-conditions.html.

